

LUMAX
LIGHTING®

CILLED

Commercial / Industrial Linear LED Luminaire



**High Lumen, High Performance
Linear High / Low Bay**

***Ideal For Warehouse, Factory and Other Commercial and
Industrial High Bay or Low Bay Environments***



CILLED

**Suspended and
“Close to Surface”
Mounting Options
(spacer brackets Required)**

2’, 4’ 6’ and 8’ Sizes

Shown here with optional
integrated sensor

Standard Performance Chart

Lumen package	Fixture size	3000K CCT			3500K CCT			4000K CCT			5000K CCT		
		Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW
79L	23	7,968	67	119	8,216	67	123	8,382	67	125	8,464	67	126
94L		9,461	82	115	9,461	82	115	9,953	82	121	10,051	82	123
94L	46	9,461	82	115	9,461	82	115	9,953	82	121	10,051	82	123
106L		10,684	95	112	11,017	95	116	11,240	95	118	11,351	95	119
146L		14,691	123	119	15,150	123	123	15,455	123	126	15,608	123	127
166L		16,616	141	118	17,134	141	122	17,479	141	124	17,653	141	125
170L	92	17,012	145	117	17,542	145	121	17,896	145	123	18,073	145	125
189L		18,922	164	115	18,922	164	115	19,906	164	121	20,101	164	123
213L		21,368	190	112	22,034	190	116	22,480	190	118	22,702	190	119

HE – High Efficacy Performance Chart

Lumen package	Fixture size	3000K CCT			3500K CCT			4000K CCT			5000K CCT		
		Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW
100L	23	10,054	74	136	10,298	74	139	10,445	74	141	10,695	74	145
120L		12,008	91	132	12,300	91	135	12,475	91	137	12,774	91	140
120L	46	12,008	91	132	12,300	91	135	12,475	91	137	12,774	91	140
134L		13,477	103	131	13,804	103	134	14,001	103	136	14,337	103	139
152L		15,220	110	138	15,589	110	142	15,810	110	144	16,189	110	147
172L		17,221	125	138	17,639	125	141	17,889	125	143	18,318	125	147
185L		18,505	135	137	18,953	135	140	19,224	135	142	19,684	135	146
209L		20,992	156	135	21,502	156	138	21,808	156	140	22,330	156	143
304L	69	30,450	225	135	31,190	225	139	31,633	225	141	32,393	225	144
324L		32,492	242	134	33,281	242	138	33,747	242	139	34,563	242	143
344L		34,443	258	134	35,269	258	137	35,771	258	139	36,628	258	142
215L	92	21,508	160	134	22,030	160	138	22,343	160	140	22,879	160	143
240L		24,016	182	132	24,600	182	135	24,950	182	137	25,548	182	140
269L		26,954	206	131	27,608	206	134	28,002	206	136	28,674	206	139
370L		37,010	270	137	37,906	270	140	38,448	270	142	39,368	270	146
419L		41,984	312	135	43,004	312	138	43,616	312	140	44,660	312	143

