



LGWLED

Lensed Grid Wet Location Luminaire



**Use in Schools, Lockers rooms,
Kitchens, Cafeterias, Restrooms
and other commercial/industrial
spaces where fixtures can be
subjected directly to water.**



LGWLED

Lensed Grid Wet Location

- DIE-FORMED CODE GAUGE COLD ROLLED STEEL HOUSING AND ENDS. EMBOSSED FOR STRENGTH AND UNIFORMITY. HEAVY-DUTY ENDS ATTACH TO HOUSING WITH INTERLOCKING TABS. INTEGRATED EQ CLIPS.
- DOOR FRAMES AVAILABLE IN FLUSH ALUMINUM. GASKETED TO PREVENT LIGHT LEAKAGE AND WATER ENTERING FIXTURE. STEEL HINGES AND ROTARY-ACTION CAM LATCHES. LATCHING/HINGING REVERSIBLE; DOOR FRAME EASILY REMOVED WITHOUT TOOLS.

Lumen package	Fixture size	3000K CCT			3500K CCT			4000K CCT			5000K CCT		
		Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW	Delivered Lumens	Input Watts	LPW
22L	2X2	2,287	21	109	2,326	21	111	2,403	21	114	2,475	21	118
32L		3,295	31	106	3,350	31	108	3,461	31	112	3,565	31	115
42L		4,264	39	109	4,336	39	111	4,479	39	115	4,614	39	118
57L		5,766	53	109	5,863	53	111	6,057	53	114	6,238	53	118
35L	2X4	3,501	29.0	121	3,560	29.0	123	3,677	29.0	127	3,788	29.0	131
48L		4,874	44.0	111	4,956	44.0	113	5,119	44.0	116	5,273	44.0	120
65L		6,590	61.0	108	6,700	61.0	110	6,922	61.0	113	7,129	61.0	117
73L		7,340	69.0	106	7,464	69.0	108	7,710	69.0	112	7,942	69.0	115
80L		8,022	67.0	120	8,157	67.0	122	8,426	67.0	126	8,679	67.0	130
97L		9,783	86.0	114	9,947	86.0	116	10,276	86.0	119	10,584	86.0	123
115L		11,532	106.0	109	11,725	106.0	111	12,113	106.0	114	12,476	106.0	118

